


# °dot



material aluminium coated  
 weight 80gr / 0.17lb  
 voltage 24Vdc  
 cri >90  
 wattage 3,6W  
 dali not supported  
 rotation 4 steps of 90°  
 inclination 90°  
 certifications CE, ENEC  
 classifications IP20




## DOT.L.B.D.V

Led	<b>WW</b> <b>WW2</b> <b>NW2</b>	2700K   3,6W   100 lm - 2353 cd - 8° 3000K   3,6W   105 lm - 2670 cd - 8° 4000K   3,6W   110 lm - 2800 cd - 8°
Body color	<b>BK</b> <b>WH</b> <b>AL</b>	black matt ral 9011 white matt ral 9016 aluminium color ral 9006 (on request only)
Dimming	<b>OC</b>	track overall control. dimming possible with 0/1-10V, potentiometer, on 2 circuits (see pag. 76)
Version	<b>T</b> <b>BI</b>	track mount built in monopoint (plasterkit required)
Accessories	<b>PL.DOT</b>	monopoint plasterkit °dot

# °dot turn <sup>NEW</sup>

material aluminium coated  
 weight 170gr / 0.37lb  
 voltage 24Vdc  
 cri >90  
 wattage 3W  
 dali supported DT6  
 rotation 355°  
 inclination 90°  
 certifications CE   
 classifications IP20 



## DOT.TURN.L.B.D.V

Led	<b>WW</b>	2700K   3,6W   100 lm - 2353 cd - 8°
	<b>WW2</b>	3000K   3,6W   105 lm - 2670 cd - 8°
	<b>NW2</b>	4000K   3,6W   110 lm - 2800 cd - 8°
Body color	<b>BK</b>	black matt ral 9011
	<b>WH</b>	white matt ral 9016
	<b>AL</b>	aluminium color ral 9006 (on request only)
Dimming	<b>IC</b>	fixtures individually dimmable, controlled by DALI DT6 track overall control. dimming possible with 0/1-10V, potentiometer, on 2 circuits (see pag. 76)
	<b>OC</b>	
Version	<b>T</b>	track mount
	<b>BI</b>	built in monopoint (plasterkit required)
Accessories	<b>PL.DOTTURN</b>	monopoint plasterkit °dot turn

# power supply 24Vdc

PS.24.XX.SM.HLG 1-10V dimming, CE, cUL certified, 90-305VAC

40	W	171*61.5*36.8 mm (L*W*H)
60	W	171*61.5*36.8 mm
80	W	195.6*61.5*38.8 mm
100	W	220*68*38.8 mm
150	W	228*68*38.8 mm
240	W	244.2*68*38.8 mm
320	W	252*90*43.8 mm
600	W	280*144*48.5mm

DAP04 dali adaptor for dali control of power supply HLG (165\*46\*23 mm)


PS.24.XX.SM.ELG 0-10V dimming, CE, cUL, CCC certified, 110-305VAC

at 240V	at 110V	
75W	60W	180*63*35.5mm (L*W*H)
100W	70W	199*63*35.5mm
150W	105W	219*63*35.5mm
200W	150W	244*71*37.5mm
240W	180W	244*71*37.5mm

PS.24.XX.SM.ELG.DA DALI dimming, CE, cUL, CCC certified, 110-305VAC

at 240V	at 110V	
75W	60W	180*63*35.5mm (L*W*H)
100W	70W	199*63*35.5mm
150W	105W	219*63*35.5mm
200W	150W	244*71*37.5mm
240W	180W	244*71*37.5mm

PS.24.SM.B.DIM Potentiometer dimming button (0-10V/1-10V)



LDIM.24V DIN rail mount dimmodule 24 VDC Max 240W controlled by 0/1-10V or potentiometer (width 25mm)

